

TECHNICAL SPECIFICATIONS ECG-7MVR

AC RATING	125V/15A//1875W/60HZ	
HOUSING	ABS High Impact Plastic	
COLOR	Black	
SOCKETS (TOTAL)	7	
POWER CABLE LENGTH (EXPOSED)	3 FT AWG 14/3 SJT	
POWER CABLE JACKET MATERIAL	PVC	
POWER CABLE CONDUCTOR SPECIFICATION	14/3 SJT	
AC PLUG STYLE	NEMA 5-15 Right Angle Plug	
OVERLOAD PROTECTION	15A Circuit Breaker	
ON-OFF SWITCH	No	
POWER SAFETY SHUT DOWN	1 x 15A Thermal Fuses	
THERMAL PROTECTION FOR MOVs	1 x 15A Thermal Fuses	
METAL OXIDE VARISTOR	L - N	2x20 mm 201KD@350J+
	L - G	1x20 mm 201KD@350J+
	N - G	1x20 mm 201KD@350J+
AC CIRCUIT TOTAL JOULES:	1400J	
MAXIMUM SPIKE CURRENT (TOTAL)	37,000A	
MAXIMUM SPIKE VOLTAGE	6KV	
MOV CLAMPING VOLTAGE	400V L-N, 500V L-G, N-G	
RESPONSE TIME <1 NANOSECOND	Yes	
SURGE INDICATOR (Protected)	Yes - 1 x Red LED	
GROUNDING INDICATOR (WIRE FAULT)	Yes - 1 X Green LED	
EM1 / RF1 NOISE FILTER	X2 CAPACITOR	1 x 0.1uF
	COIL	N/A
	FREQUENCY	100K Hz ~ 50M Hz
	ATTENUATION	Up to 50 dB Reduction
START CONTROL OUTLET POWER	16W~30W	
STANDBY POWER CONSUMPTION	<1W Idle Current Draw	
PACKAGING STYLE	Four-Color Carton	
USER MANUAL & WARRANTY SHEET	Enclosed	
BAR CODE LABEL ON CASE PACK	Yes = 8 5583 00006 3	
CASEPACK QUANTITY	16 PCS - Master Carton	
STANDARD EXPORT CARTON DESIGN	Yes	
AGENCY CERTIFICATIONS	UL/cUL	

BITS #	ECG-7MVR	Unit	Unit Dims (cm)			Qty	Color Box Dims (cm)			G. W
		Unit Dim	L	W	H	pcs	L	W	H	KGS
DESCRIPTION		1	31.5	7.1	3.8	1	42.5	13.2	5.8	
7 Outlet Advanced Power Strip, 1400J, 3ft SJT Cord, Right Angle Plug	Unit	Unit Dims (in)			Master Carton	Master Carton Dims (cm)			G.W.	
		L	W	H	pcs	L	W	H	KGS	
	1	12.5	2.75	1.5	16					
	CONTAINER - 20'		QTY	12,984		Inner Qty	Color Box Dims (in)			G.W.
	CONTAINER - 40'		QTY	26,376		pcs	L	W	H	LBS
			16.75	5.25	2.25					
Master Carton	Master Carton Dims (in)			G.W.						
pcs	L	W	H	LBS						
16										

